





SX 14

SITE SPECIFICATIONS

- BAY HEIGHT: 77" rise plus vehicle
- BAY WIDTH: 14' recommended
- BAY DEPTH: 28' rec. standard
- POWER REQ.: 208-230v Single Phase*, 30-amp breaker
- MIN. CONCRETE SPEC: 4" thick, reinforced, free from cracks/seams, rated at 3500+ psi, cured at least 28 days

Model Number	SX14	SX14-R
Lifting Capacity	14,000 lbs.	
Rise Height	77"	66.5″
Overall Length	265″	219″
Overall Width	91.25"	
Width of Runways	25.5"	
Between Runways	40"	
Lowered Height	10.5″	-
Maximum Wheelbase	183″	
Wheel Alignment (Max.)	176″	
Wheel Alignment (Min.)	70.75	
Motor	ЗНР	
Voltage (Single Phase Std.)	208v-240v (23 FLA)	
Speed of rise	75 s	
Air Required	90 - 120 psi (20 CFM)	
Min. Recommended Bay Size	14' x 28'	14'x 24'
ALI/ETL Certified	√	✓
Color Available	I	

^{*3-}phase upgrade is available for purchase

Extended Ramps add 18" to \$X14

www.challengerlifts.com 1-800-648-5438