ST 1065FXV

Hydraulic mobile column lift

The ST 1065FXV mobile column lift is specifically designed to lift vehicles with **large wheel diameters**, such as wheel loaders, graders, tow-tugs, mining vehicles, mobile cranes and other heavy industrial vehicles.



Large wheel diameters

The pick-up fork of the ST 1065FXV is 500 mm long and 770 mm wide, making it possible to lift vehicles with a wheel diameter up to 1800 mm. For vehicles with a wheel diameter between 1000 mm - 1300 mm, one reducer plate is required. Two reducer plates are required to pick-up vehicles with a wheel diameter between 800 mm - 1000 mm.

Lifting capacity

Each column has a max. lifting capacity of 6.500 kg. Up to 28 columns can be used in a set up, making it possible to lift extremely heavy and multi-axled vehicles. The microprocessor controlled lifting system ensures full synchronisation during raising and lowering of the columns. The exact tracking offers unique advantages. -Individual and paired operation from the column concerned.

-Operation of the system from every column.

2-speed lowering

The ST 1065FXV is equipped with 2 selectable lowering speeds. The slow lowering option enables the operator to lower the vehicle accurately and more safely onto axle stands for the maintenance and repair of wheels, brakes etc.

STERTIL-KONI: YOUR HEAVY DUTY LIFTING PARTNER



Options:

- Lighting set (2 fittings)
- Remote control, including 10 meter cable
- Various custom made crossbeams
- RAL colours to customers specification

Specifications:

Lifting system : hydraulic Lifting capacity : 6.500 kg Lifting height : 1,850 mm. Lifting time : 89 sec.


Motor power : 2,2 kW per column

Maximum safety:

- Automatic overload protection
- Low voltage control cabinet
- Dead man's operation
- Independent mechanical locking system
- Microprocessor controlled synchronisation system
- Automatic stop when highest position is reached
- Splashproof electrical system (IP65)
- Emergency switch on every column

More information?

For more or specific information about the ST 1065FXV, or one of the other quality products from Stertil-Koni, please contact us for further assistance.



Stertil B.V., P.O. Box 23, 9288 ZG Kootstertille (The Netherlands) Tel. +31(0)512 334444 Telefax +31(0)512334430

E-mail: info@stertil-nl Internet: www.stertil-koni.nl

